Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Qualitätssicherung, Oberlaaerstraße 284, 1230 Wien, AT

Model identifier: LED 3n 3W SMD(26pcs) D500x20mm 1/4 3000K

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

Type of light source.			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	LED module		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	parameters:	
Energy consumption in an	2	Francis officionas	

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
	nption in on- 00 h), rounded st integer	3	Energy efficiency class	С	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P _{on}), expressed in W		2,8	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	390	Spectral power dis-	See image	
sions without	Width	20	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	1	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,437		
		nates (x and y)	0,403		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	12	Survival factor	1,00		
the lumen maintenance factor	0,96				


(a)'-': not applicable; (b)'-': not applicable;




Page 17 of 20



Test Data Sheet 7: Luminous intensity distribution diagram



Test Data Sheet 8: Spectral power distribution



Waltek Testing Group (Foshan) Co., Ltd. http://www.waltek.com.cn

WT-510-201-12-A