

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ORION

Supplier's address: Qualitätssicherung, Oberlaaerstraße 284, 1230 Wien, AT

Model identifier: LED 6z 6W SMD(36pcs) 450x7mm Band 3000K

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	LED module		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	470 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	6,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Outer dimensions without separate control gear, lighting control	Height	450	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	7	
	Depth	1	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,440 0,405
Parameters for directional light sources:			
Peak luminous intensity (cd)	210	Beam angle in degrees, or the range of beam angles that can be set	160
Parameters for LED and OLED light sources:			
R9 colour rendering index value	8	Survival factor	1,00
the lumen maintenance factor	0,96		

(a): not applicable;

(b): not applicable;



Clause	Requirement + Test	Result – Remark	Verdict
--------	--------------------	-----------------	---------

Parameters for LED and OLED light sources:			
R9 colour rendering index value	8	Survival factor	1,00
the lumen maintenance factor	0.96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ 1)	0.967	Colour consistency in McAdam ellipses	1.4
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0.9	Stroboscopic effect metric (SVM)	0.4

"-" not applicable;

Attachment : Photometric test record:

