

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ORION

Supplier's address: Qualitätssicherung, Oberlaaerstraße 284, 1230 Wien, AT

Model identifier: LED 17d 17W SMD(17pcs) 480x20mm 3000K

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	LED module		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	17	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 815 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	17,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Outer dimensions without separate control gear, lighting control	Height	480	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	20	
	Depth	2	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,435 0,403
Parameters for directional light sources:			
Peak luminous intensity (cd)	990	Beam angle in degrees, or the range of beam angles that can be set	160
Parameters for LED and OLED light sources:			
R9 colour rendering index value	7	Survival factor	1,00
the lumen maintenance factor	0,96		

(a): not applicable;

(b): not applicable;



BST Testing (Shenzhen) Co.,Ltd.


Report No.: BSTXD221022747425SR

Clause	Requirement + Test	Result – Remark	Verdict
--------	--------------------	-----------------	---------

Parameters for LED and OLED light sources:			
R9 colour rendering index value	7	Survival factor	1.00
the lumen maintenance factor	0.96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ 1)	0.990	Colour consistency in McAdam ellipses	3.5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0.9	Stroboscopic effect metric (SVM)	0.4

¹⁰-¹¹ not applicable;

Attachment : Photometric test record:



Add: No.7, New Era Industrial Zone, Guantian, Bao'an District, Shenzhen, Guangdong, China
 Certificate Search: <http://www.bst-lab.com>, Tel:400-882-6168, 8009990305, E-mail:christina@bst-lab.com