Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	ORION	
--------------------------------	-------	--

Supplier's address: Qualitätssicherung, Oberlaaerstraße 284, 1230 Wien, AT

Model identifier: LED 23u 23W SMD(224pcs) Dm165mm 2200-6000K

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED module				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					
Darameter	Malua	Darameter	Value		

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consur mode (kWh/10 up to the neares	00 h), rounded	23	Energy efficiency class	F	
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	2 420 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	22006000	
On-mode pow pressed in W	ver (P _{on}), ex-	23,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
(P _{net}) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90	
Outer dimen-	Height	1	Spectral power dis-	See image	
sions without	Width	165	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	165	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,506		
		nates (x and y)	0,415		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	50	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

